

View Online at <https://aerobasegroup.com/nsn/5930-00-985-0437>

Thread Class:

2a 1st mounting facility

Thread Length:

0.297 inches 1st mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.062 inches

Overall Height:

2.750 inches

Overall Width:

2.625 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.515 inches single actuator

Unthreaded Mounting Hole Diameter:

0.172 inches 2nd mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

2.000 inches 2nd mounting facility

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing 1st mounting facility

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0