

View Online at <https://aerobasegroup.com/nsn/5930-00-985-4339>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant and fungus resistant

**Overall Length:**

1.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.531 inches

**Overall Height:**

4.500 inches

**Overall Width:**

0.940 inches

**Body Width:**

0.938 inches

**Body Height:**

1.188 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.912 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

1.230 inches

**Actuator Position-action Relationship:**

Center position maintained and down position momentary and up position maintained

**Actuator Position-locking Relationship:**

Center position no locking action and down position no locking action and up position locked in

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

48

**Pile-up Contact Form Arrangement:**

1a 2nd position

**Thread Size:**

0.099 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Precious Material And Location:**

Springs and contacts silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0