## NSN 5930-00-986-3393

Rotary Switch - Page 1 of 1



3393

View Online at https://aerobasegroup.com/nsn/5930-00-986-3
Hazardous Locations/environmental Protection:
Dustproof
<b>Unthreaded Mounting Hole Diameter:</b>
0.190 inches single mounting facility
Individual Section Quantity:
15
Longest Horizontal Distance Between Mounting Centers:
2.298 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.298 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Base single mounting facility
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

No

Fiig:

A052b0