## NSN 5930-00-986-3394

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-986-3394

Dustproof  Overall Length:  9.156 inches Individual Section Quantity:  20  Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity:  1 each section rear Throw Quantity:  2 each section rear Mounting Method:
9.156 inches Individual Section Quantity: 20 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 2 each section rear
Individual Section Quantity: 20 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 2 each section rear
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 2 each section rear
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section rear Throw Quantity: 2 each section rear
Nonpile-up symmetrical  Pole Quantity:  1 each section rear  Throw Quantity:  2 each section rear
Pole Quantity:  1 each section rear  Throw Quantity:  2 each section rear
1 each section rear  Throw Quantity: 2 each section rear
Throw Quantity: 2 each section rear
2 each section rear
Mounting Method:
mounting method:
Threaded bushing single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, square single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Etter.
Fiig: