

View Online at <https://aerobasegroup.com/nsn/5930-00-986-3397>

Thread Class:

2b 1st mounting facility

Thread Length:

0.500 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

13.344 inches

Shaft Length:

1.344 inches single actuator

Overall Diameter:

3.750 inches

Individual Section Quantity:

25

Longest Horizontal Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

3 each section front

Mounting Method:

Bracket 1st mounting facility and threaded hole 1st mounting facility

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unef 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0