Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-986-3399

| Hazardous Locations/environmental Protection: |
|---|
| Watertight |
| Overall Length: |
| 4.125 inches |
| Overall Height: |
| 2.781 inches |
| Overall Width: |
| 2.469 inches |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.125 inches single actuator |
| Individual Section Quantity: |
| 10 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| 103605a-2a |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.281 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.281 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 1 each section front |
| Mounting Method: |
| Base single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 120.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |

NSN 5930-00-986-3399 Rotary Switch - Page 2 of 2

| Shaft Type: |
|---|
| Round single actuator |
| Terminal Type: |
| Screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 10.0 amperes resistive load dc at sea level |
| Style Designator: |
| Tap, circuit selector |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |
| |
| |

