NSN 5930-00-986-8606

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-986-8606 | |
|---|--|
| Body Style: | |
| Panel mounted | |
| Overall Length: | |
| 4.188 inches | |
| Overall Height: | |
| 1.200 inches | |
| Overall Width: | |
| 0.960 inches | |
| Body Width: | |
| 0.960 inches | |
| Body Height: | |
| 1.200 inches | |
| Actuator Length: | |
| 1.035 inches | |
| Actuator Style: | |
| Rectangular | |
| Actuator Height: | |
| 0.188 inches | |
| Actuator Width: | |
| 0.735 inches | |
| Actuator Color: | |
| White single actuator | |
| Illuminated Actuator Color: | |
| Green single actuator and white single actuator | |
| Actuator Inscription: | |
| Operate single actuator | |
| Maximum Voltage Rating In Volts: | |
| 250.0 ac and 30.0 dc | |
| Mounting Surface To Terminal End Distance: | |
| 3.125 inches | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Panel | |
| Features Provided: | |
| Full display lens and holding solenoid | |

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

 $5.000 \ \text{amperes}$ resistive dc and $3.000 \ \text{amperes}$ inductive dc and $5.000 \ \text{amperes}$ resistive ac

Precious Material And Location:

Terminal surfaces and contacts silver

NSN 5930-00-986-8606

Push Switch - Page 2 of 2



| Terminal Type And Quantity | Terminal | Type | And | Quantity |
|----------------------------|----------|------|-----|----------|
|----------------------------|----------|------|-----|----------|

6 turret and 7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0