NSN 5930-00-986-8634

Push Switch - Page 1 of 2



Body Style: Panel mounted Overall Length: 4.188 inches Overall Height: 1.200 inches Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.735 inches Actuator Vidth: 0.735 inch	View Online at https://aerobasegroup.com/nsn/5930-00-986-8634
Overall Length: 4.188 inches Overall Height: 1.200 inches Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Vidith: 0.735 inches Actuator Color: White single actuator and red Single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 de Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Body Style:
4.188 inches Overall Height: 1.200 inches Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Body Height: 1.200 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Style: Rectangular Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator White single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: Inclosure Type: Fully enclosed Mounting Method:	Panel mounted
Overall Height: 1.200 inches Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Overall Length:
1.200 inches Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Width: 0.755 inches Actuator Width: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 de Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	4.188 inches
Overall Width: 0.960 inches Body Width: 0.960 inches Body Height: 1.200 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 a cand 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Overall Height:
Body Width: 0.960 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Height: 0.1735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	1.200 inches
Body Width: 0.960 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Overall Width:
D.960 inches Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	0.960 inches
Body Height: 1.200 inches Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Body Width:
Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	0.960 inches
Case Material: Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Body Height:
Metal or plastic Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	1.200 inches
Actuator Length: 1.035 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Case Material:
Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Metal or plastic
Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Length:
Rectangular Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	1.035 inches
Actuator Height: 0.188 inches Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Style:
Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Rectangular
Actuator Width: 0.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Height:
O.735 inches Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	0.188 inches
Actuator Color: White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Width:
White single actuator Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	0.735 inches
Illuminated Actuator Color: Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Color:
Green single actuator and red single actuator Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	White single actuator
Actuator Inscription: Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Illuminated Actuator Color:
Remote a-he local a-he single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Green single actuator and red single actuator
Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Actuator Inscription:
250.0 ac and 30.0 dc Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Remote a-he local a-he single actuator
Mounting Surface To Terminal End Distance: 4.000 inches Inclosure Type: Fully enclosed Mounting Method:	Maximum Voltage Rating In Volts:
4.000 inches Inclosure Type: Fully enclosed Mounting Method:	250.0 ac and 30.0 dc
Inclosure Type: Fully enclosed Mounting Method:	Mounting Surface To Terminal End Distance:
Fully enclosed Mounting Method:	4.000 inches
Mounting Method:	Inclosure Type:
	Fully enclosed
Panel	Mounting Method:
	Panel

Features Provided:

Horizontal split lens and holding solenoid

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

NSN 5930-00-986-8634

Push Switch - Page 2 of 2



Pred	ious	Mater	ial And	d L	ocati	on:

Terminal surfaces and contacts silver

Terminal Type And Quantity:

12 turret and 7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0