

View Online at <https://aerobasegroup.com/nsn/5930-00-987-0109>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.385 inches single mounting facility

Overall Length:

Between 2.955 inches and 2.975 inches

First Flat Length:

0.300 inches single actuator and 0.320 inches single actuator

Flat Height:

0.213 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

1.300 inches single actuator and 1.320 inches single actuator

Overall Diameter:

Between 0.521 inches and 0.541 inches

Nonturn Device Radius:

0.521 inches at 3:00 o'clock and 0.531 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

240.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0