

View Online at <https://aerobasegroup.com/nsn/5930-00-987-4523>

Body Style:

Bushing mounted

Overall Length:

1.594 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Body Diameter:

Between 0.406 inches and 0.426 inches

Bushing Length:

Between 0.490 inches and 0.510 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.365 inches and 0.385 inches

Actuator Height:

Between 0.240 inches and 0.260 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 250.000 milliamperes lamp dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac and 250.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNEF

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0