NSN 5930-00-988-2762

Push Switch - Page 1 of 2

Thread Class:

Body Style:

2a



View Online at https://aerobasegroup.com/nsn/5930-00-988-2762

Bushing mounted
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
1.844 inches
Overall Height:
0.875 inches
Overall Width:
0.875 inches
Body Diameter:
0.562 inches
Bushing Length:
0.750 inches
Body Length:
0.422 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.875 inches
Actuator Height:
0.281 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action single switch unit

NSN 5930-00-988-2762

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0