## NSN 5930-00-988-7462

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-988-7462

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

10.500 inches

**Shaft Length:** 

1.125 inches single actuator

**Overall Diameter:** 

3.750 inches

**Individual Section Quantity:** 

15

**Longest Horizontal Distance Between Mounting Centers:** 

2.297 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.297 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

3 each section front

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

**Square Shaft Size:** 

0.250 inches single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Makes before breaks each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-00-988-7462

Rotary Switch - Page 2 of 2



Contact L	oad Cur	rent Rating:
-----------	---------	--------------

10.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, panel mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A052b0