

View Online at <https://aerobasegroup.com/nsn/5930-00-988-9068>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

Between 0.496 inches and 0.515 inches

Overall Height:

Between 1.348 inches and 1.465 inches

Overall Width:

Between 0.246 inches and 0.265 inches

Bushing Length:

Between 0.239 inches and 0.253 inches

Body Length:

Between 0.496 inches and 0.515 inches

Body Width:

Between 0.246 inches and 0.265 inches

Body Height:

Between 0.313 inches and 0.337 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.120 inches and 0.130 inches

Actuator Height:

Between 0.631 inches and 0.677 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 0.478 inches and 0.535 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0