

View Online at <https://aerobasegroup.com/nsn/5930-00-988-9068>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.496 inches and 0.515 inches

**Overall Height:**

Between 1.348 inches and 1.465 inches

**Overall Width:**

Between 0.246 inches and 0.265 inches

**Bushing Length:**

Between 0.239 inches and 0.253 inches

**Body Length:**

Between 0.496 inches and 0.515 inches

**Body Width:**

Between 0.246 inches and 0.265 inches

**Body Height:**

Between 0.313 inches and 0.337 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.120 inches and 0.130 inches

**Actuator Height:**

Between 0.631 inches and 0.677 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

Between 0.478 inches and 0.535 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0