

View Online at <https://aerobasegroup.com/nsn/5930-00-989-4285>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

2.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.797 inches and 1.827 inches

Overall Height:

4.059 inches

Overall Width:

1.531 inches

Body Length:

2.156 inches

Body Width:

1.531 inches

Body Height:

2.091 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 0.844 inches and 0.906 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

80.000 amperes resistive dc and 30.000 amperes inductive dc and 7.000 amperes lamp dc and 30.000 amperes resistive ac and 20.000 amperes inductive ac and 7.500 amperes lamp ac

Test Data Document:

81349-mils3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0