

View Online at <https://aerobasegroup.com/nsn/5930-00-989-4285>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

2.156 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.797 inches and 1.827 inches

**Overall Height:**

4.059 inches

**Overall Width:**

1.531 inches

**Body Length:**

2.156 inches

**Body Width:**

1.531 inches

**Body Height:**

2.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.235 inches and 0.245 inches

**Actuator Height:**

Between 0.844 inches and 0.906 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

80.000 amperes resistive dc and 30.000 amperes inductive dc and 7.000 amperes lamp dc and 30.000 amperes resistive ac and 20.000 amperes inductive ac and 7.500 amperes lamp ac

**Test Data Document:**

81349-mils3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A053a0