

View Online at <https://aerobasegroup.com/nsn/5930-00-989-7830>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.872 inches and 0.878 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

0.400 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Unthreaded Mounting Hole Diameter:**

0.115 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.403 inches and 0.409 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.119 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0