

View Online at <https://aerobasegroup.com/nsn/5930-00-990-0119>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Water resistant

Overall Length:

0.840 inches

Overall Height:

2.628 inches

Overall Width:

0.984 inches

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.984 inches

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

1.448 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0