NSN 5930-00-990-0502



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-990-0502 **Body Style:** Hole mounted **Overall Length:** 1.480 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Height:** 0.900 inches **Overall Width:** 0.400 inches **Body Length:** 1.094 inches **Body Width:** 0.400 inches **Body Height:** 0.625 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.114 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.406 inches **Actuator Length:** 0.110 inches **Actuator Style:** Rectangular **Actuator Width:** 0.170 inches **Actuator Free Position Height:** 0.625 inches **Maximum Voltage Rating In Volts:** 277.0 ac and 250.0 dc **Inclosure Type:**

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Criticality Code Justification:

Feat

NSN 5930-00-990-0502 Sensitive Switch - Page 2 of 2



Switch Actuating Force:
8.0 ounces
Actuator Movement:
0.047 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
0.250 amperes resistive dc and 11.000 amperes resistive ac
Special Features:
Weapon system essential
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 quick disconnect, male or 3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A053a0