NSN 5930-00-990-5422

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-990-5422

The transfer of the poly, acres access to a process which
Thread Length:
0.375 inches single mounting facility
Overall Length:
1.562 inches
Overall Height:
1.531 inches
Overall Width:
1.312 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.125 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.875 inches single actuator
Individual Section Quantity:
1
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
5 single section front
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Contact Load Current Rating:

Contact Load Current Rating

1.0 amperes resistive load dc at sea level

NSN 5930-00-990-5422

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0