

View Online at <https://aerobasegroup.com/nsn/5930-00-991-0619>

Thread Class:

2a single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Shaft Length:

1.344 inches single actuator

Unthreaded Mounting Hole Diameter:

0.190 inches single mounting facility

Individual Section Quantity:

25

Longest Horizontal Distance Between Mounting Centers:

2.298 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.298 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0