

View Online at <https://aerobasegroup.com/nsn/5930-00-991-3375>

Thread Class:

3a single threaded bushing

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

2.438 inches

Body Length:

0.782 inches

Overall Diameter:

0.875 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 600.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

3.00 differential point degrees fahrenheit and 99.00 actuation point degrees fahrenheit and 96.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0