

View Online at <https://aerobasegroup.com/nsn/5930-00-991-3482>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Width Between Flats:

0.185 inches single actuator and 0.187 inches single actuator

Overall Length:

1.406 inches

Overall Height:

1.328 inches

Overall Width:

1.297 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.313 inches single actuator

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Clips and contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0