NSN 5930-00-991-8630



Sensitive Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-00-991-8630

Thread Class: 2a **Body Style:** Hole mounted Hazardous Locations/environmental Protection: Dustproof and oiltight **Overall Length:** 1.531 inches **Overall Width:** 2.438 inches **Actuator Style:** Roller plunger **Actuator Roller Diameter:** 0.500 inches **Housing Height:** 1.781 inches **Housing Width:** 1.531 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.344 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.156 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 600.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole **Thread Size:** 0.190 inches **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Actuating Force:**

88.0 inch-ounces

Actuator Movement:

0.125 pretravel inches and 0.250 overtravel inches and 0.078 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.100 amperes resistive dc and 12.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unf

NSN 5930-00-991-8630

Sensitive Switch - Page 2 of 2



Terminal Type And Quar	ntity:
8 wire lead	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0