## NSN 5930-00-991-8633

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-991-8633

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
4.563 inches
Overall Height:
1.781 inches
Overall Width:
1.531 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.375 inches
Housing Height:
1.781 inches
Housing Width:
1.531 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Actuating Force:
56.0 ounces
Actuator Movement:

0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc and 1.200 amperes resistive ac

**Precious Material And Location:**Contacts silver

**Terminal Type And Quantity:** 

4 screw

## NSN 5930-00-991-8633

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0