NSN 5930-00-991-8634

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-991-8634

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
4.844 inches
Overall Height:
2.437 inches
Overall Width:
1.531 inches
Case Material:
Metal
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.781 inches
Housing Width:
1.531 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
3 two circuit, two positions momentary single switch unit
Switch Actuating Force:
68.0 ounces
Actuator Movement:
4.5 pretravel degrees and 56.0 overtravel degrees and 2.3 differential degrees

Contact Load Current Rating At Maximum Rated Voltage: 100.000 milliamperes resistive dc and 1.200 amperes resistive ac

NSN 5930-00-991-8634 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
12 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0