NSN 5930-00-991-8652

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-991-8652 **Thread Class:** 2a **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof and oiltight **Overall Length:** 7.094 inches **Overall Height:** 2.656 inches **Overall Width:** 1.531 inches **Case Material:** Metal **Actuator Length:** Between 1.188 inches and 3.000 inches **Actuator Style:** Roller arm **Actuator Roller Diameter:** 1.500 inches **Actuator Roller Width:** 0.250 inches **Housing Height:** 1.781 inches **Housing Width:** 1.531 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 2.344 inches** Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.156 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 600.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole **Thread Size:**

0.190 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

72.0 inch-ounces

NSN 5930-00-991-8652

Sensitive Switch - Page 2 of 2



Actuator	Movement:
----------	-----------

4.5 pretravel degrees and 56.0 overtravel degrees and 2.25 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 12.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0