

View Online at <https://aerobasegroup.com/nsn/5930-00-991-8652>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and oiltight

Overall Length:

7.094 inches

Overall Height:

2.656 inches

Overall Width:

1.531 inches

Case Material:

Metal

Actuator Length:

Between 1.188 inches and 3.000 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

1.500 inches

Actuator Roller Width:

0.250 inches

Housing Height:

1.781 inches

Housing Width:

1.531 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

72.0 inch-ounces

Actuator Movement:

4.5 pretravel degrees and 56.0 overtravel degrees and 2.25 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 12.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0