NSN 5930-00-992-4695

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-992-4695

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.411 inches single mounting facility

Overall Length:

1.875 inches

Overall Height:

Between 1.422 inches and 1.516 inches

Overall Width:

1.422 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.869 inches single actuator and 0.891 inches single actuator

Nonturn Device Radius:

0.375 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

NSN 5930-00-992-4695

Rotary Switch - Page 2 of 2



| | T | 'nr | ead | Series | Desig | nator: |
|--|---|-----|-----|--------|-------|--------|
|--|---|-----|-----|--------|-------|--------|

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0