NSN 5930-00-992-5080



Pressure Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-992-5080 **Thread Class:** 2b all threaded hole **Overall Length:** 2.641 inches **Overall Height:** 2.641 inches **Overall Width:** 0.922 inches **Distance Between Mounting Facility Centers:** 0.688 inches **Pressure Switch Type:** Gage **Mounting Method:** Base and threaded hole **Features Provided:** Capillary tube end seal connection Thready Qty Per Inch (tpi): 32 all threaded hole **Contact Action Stimulus:** Decrease **Thread Size:** 0.138 inches all threaded hole **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Screw **Contact Load Current Rating:** 8.0 amperes resistive load first voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

350.00 actuation point pounds per square inch and 400.00 deactuation point pounds per square inch and 50.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

NSN 5930-00-992-5080

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0