NSN 5930-00-992-5080

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-992-5080

View Online at https://aerobasegroup.com/nsi//3500-00-392-3000
Thread Class:
2b all threaded hole
Overall Length:
2.641 inches
Overall Height:
2.641 inches
Overall Width:
0.922 inches
Distance Between Mounting Facility Centers:
0.688 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and threaded hole
Features Provided:
Capillary tube end seal connection
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Decrease
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
8.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
350.00 actuation point pounds per square inch and 400.00 deactuation point pounds per square inch and 50.00 differential point pounds
per square inch
Contact Voltage Rating In Volts:
240.0 ac at sea level first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unc all threaded hole

NSN 5930-00-992-5080

Pressure Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0

