

View Online at <https://aerobasegroup.com/nsn/5930-00-992-7398>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.296 inches single mounting facility and 0.328 inches single mounting facility

**Overall Length:**

2.031 inches

**Overall Height:**

2.000 inches

**Overall Width:**

2.000 inches

**First Flat Length:**

0.297 inches single actuator and 0.327 inches single actuator

**Shaft Diameter:**

0.251 inches single actuator

**Shaft Length:**

0.719 inches single actuator and 0.781 inches single actuator

**Nonturn Device Radius:**

0.485 inches at 12: 00 o'clock and 0.515 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

8 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Shaft Flat/slot Angular Location:**

90.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, nonparallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+30.000/+198.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0