

View Online at <https://aerobasegroup.com/nsn/5930-00-992-7400>

Thread Class:

2a single mounting facility

Thread Length:

0.296 inches single mounting facility and 0.328 inches single mounting facility

Overall Length:

2.031 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

First Flat Length:

0.297 inches single actuator and 0.327 inches single actuator

Shaft Diameter:

0.251 inches single actuator

Shaft Length:

0.719 inches single actuator and 0.781 inches single actuator

Nonturn Device Radius:

0.485 inches at 12: 00 o'clock and 0.515 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, nonparallel flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+30.000/+198.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0