

View Online at <https://aerobasegroup.com/nsn/5930-00-993-1411>

Thread Length:

0.625 inches single threaded bushing

Overall Length:

6.405 inches

Body Length:

4.833 inches

Overall Diameter:

3.750 inches

Bulb Length:

2.968 inches

Bulb Diameter:

Between 0.618 inches and 0.625 inches

Temperature Sensing Element Type:

Bulb

Width Across Flats:

0.875 inches

Mounting Method:

Threaded bushing

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+400.00 actuation point degrees fahrenheit and -100.00/+400.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point dial and external actuation point dial

Contact Stimulus Rating:

60.00 actuation point degrees celsius and 55.00 deactuation point degrees celsius and 5.00 differential point degrees celsius

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Uns single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0