

View Online at <https://aerobasegroup.com/nsn/5930-00-993-3986>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Flame resistant

**Overall Length:**

1.265 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.497 inches and 0.503 inches

**Overall Height:**

1.015 inches

**Overall Width:**

0.702 inches

**Body Length:**

1.265 inches

**Body Width:**

0.515 inches

**Body Height:**

0.890 inches

**Case Material:**

Plastic

**Actuator Length:**

Between 0.235 inches and 0.265 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.125 inches

**Actuator Width:**

Between 0.281 inches and 0.311 inches

**Actuator Free Position Height:**

Between 0.495 inches and 0.515 inches

**Actuator Adapter Style:**

Pushbutton

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

38.8 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 6.000 amperes motor ac

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0