NSN 5930-00-993-4654

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-993-4654

Body Style:
Hole mounted
Overall Length:
1.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
0.625 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.438 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.100 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.406 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
2.5 ounces
Actuator Movement:

Between 0.045 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

NSN 5930-00-993-4654

Sensitive Switch - Page 2 of 2



Contact Load	l Current	Rating	At Maximum	Rated	Voltage:
Juliaul Luai	a Guileii	ivatiliy	AL WIGAIIIIUIII	Nateu	V Oitage.

3.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0