

View Online at <https://aerobasegroup.com/nsn/5930-00-994-3331>

**Hazardous Locations/environmental Protection:**

Vibration resistant and shock resistant

**Overall Length:**

6.960 inches

**Overall Height:**

3.000 inches

**Overall Width:**

2.570 inches

**First Flat Length:**

0.560 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.250 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.188 inches single mounting facility

**Individual Section Quantity:**

5

**Longest Horizontal Distance Between Mounting Centers:**

2.250 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.625 inches single mounting facility

**Operating Temperature Range:**

-0.0/+185.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

5 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

118.0 ac at sea level

**Shaft Flat/slot Angular Location:**

90.0 degrees from nonturn device single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, nonparallel flatted single actuator

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0