

View Online at <https://aerobasegroup.com/nsn/5930-00-994-3331>

Hazardous Locations/environmental Protection:

Vibration resistant and shock resistant

Overall Length:

6.960 inches

Overall Height:

3.000 inches

Overall Width:

2.570 inches

First Flat Length:

0.560 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

2.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.625 inches single mounting facility

Operating Temperature Range:

-0.0/+185.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

118.0 ac at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, nonparallel flatted single actuator

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0