# NSN 5930-00-994-6035

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-994-6035

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

2.445 inches

## **Overall Height:**

1.000 inches

## **Overall Width:**

0.940 inches

## First Flat Length:

0.380 inches single actuator

## Flat Height:

0.218 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

1.380 inches single actuator

## Individual Section Quantity:

2

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

## **Throw Quantity:**

9 each section front

## **Mounting Method:**

Threaded bushing single mounting facility

## Thread Size:

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

10 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section front

# Switch Actuator Positioning Increment:

36.0 degrees single actuator

# NSN 5930-00-994-6035

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0