

View Online at <https://aerobasegroup.com/nsn/5930-00-994-6058>

Thread Class:

2a single mounting facility

Thread Length:

0.234 inches single mounting facility and 0.266 inches single mounting facility

Overall Length:

Between 1.311 inches and 1.385 inches

Overall Height:

Between 1.306 inches and 1.328 inches

Overall Width:

Between 1.109 inches and 1.141 inches

First Flat Length:

0.495 inches single actuator and 0.505 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.922 inches single actuator and 0.954 inches single actuator

Nonturn Device Radius:

0.515 inches at 9:00 o'clock and 0.547 inches at 9:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section front

Throw Quantity:

2 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+2.000/+8.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0