NSN 5930-00-994-7059 Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-994-7059
Body Style:
Hole mounted
Overall Length:
1.937 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Overall Width:
0.687 inches
Body Length:
Between 1.922 inches and 1.952 inches
Body Width:
Between 0.672 inches and 0.692 inches
Body Height:
0.984 inches
Case Material:
Plastic
Actuator Style:
Round
Actuator Diameter:
0.219 inches
Actuator Free Position Height:
Between 1.085 inches and 1.135 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Uninclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
10.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.050 overtravel inches and 0.003 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000
amperes inductive ac and 1.500 amperes lamp ac
Thread Series Designator:

Unc

NSN 5930-00-994-7059

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

A053a0

Fiig: