## NSN 5930-00-994-7726

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-994-7726 **Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.313 inches **Overall Height:** 1.500 inches **Overall Width:** 1.312 inches First Flat Length: 0.375 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.248 inches single actuator and 0.251 inches single actuator **Shaft Length:** 0.875 inches single actuator **Nonturn Device Radius:** 0.438 inches at 9: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 2nd section rear **Throw Quantity:** 3 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 12.0 dc at sea level **Rotor Through Connection Quantity:** 1 each section **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** 

Round, flatted single actuator

## NSN 5930-00-994-7726

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Contact Load Current Rating:
3.5 amperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0