## NSN 5930-00-994-7734

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-994-7734

**Thread Class:** 2b single mounting facility **Overall Length:** 3.876 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches First Flat Length: 0.438 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.938 inches single actuator **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 8 each section front **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** 

Tab, solder lug

## NSN 5930-00-994-7734

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load ac at sea level
Precious Material And Location:
Terminals gold and contacts and rotors silve
Precious Material:
Gold and silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0