## NSN 5930-00-994-9360

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-994-9360

Overall Length:
1.950 inches
Outside Diameter:
0.125 inches single connection
Body Length:
0.830 inches
Overall Diameter:
0.850 inches
Pressure Switch Type:
Gage
Width Across Flats:
1.060 inches
Mounting Method:
Clamp
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
43.00 actuation point pounds per square inch and 37.00 deactuation point pounds per square inch and 6.00 differential point pounds per
square inch
Contact Voltage Rating In Volts:
24.0 dc at sea level single voltage
Pressure Connector Type:
Inverted flare, threaded external single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Terminal surfaces silver

Silver

**Precious Material:** 

## NSN 5930-00-994-9360

Pressure Switch - Page 2 of 2



Style Designator:
Cylindrical
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0