

View Online at <https://aerobasegroup.com/nsn/5930-00-995-0140>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.495 inches and 0.505 inches

Body Length:

0.786 inches

Body Width:

0.250 inches

Body Height:

0.437 inches

Unthreaded Mounting Hole Diameter:

0.089 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.078 inches and 0.108 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

Between 0.078 inches and 0.108 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

8.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0