## NSN 5930-00-996-1605

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-996-1605

Body Style:
Hole mounted
Overall Length:
1.485 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.870 inches and 0.880 inches
Overall Height:
1.431 inches
Overall Width:
0.406 inches
Body Length:
Between 1.078 inches and 1.110 inches
Body Width:
Between 0.390 inches and 0.422 inches
Body Height:
Between 0.609 inches and 0.641 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.109 inches and 0.119 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.401 inches and 0.411 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.915 inches
Actuator Roller Diameter:
Between 0.172 inches and 0.204 inches
Actuator Roller Width:
Between 0.172 inches and 0.204 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces

14.0 ounces

**Switch Actuating Force:** 

## NSN 5930-00-996-1605

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	am.	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

10.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0