

View Online at <https://aerobasegroup.com/nsn/5930-00-996-1605>

**Body Style:**

Hole mounted

**Overall Length:**

1.485 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.870 inches and 0.880 inches

**Overall Height:**

1.431 inches

**Overall Width:**

0.406 inches

**Body Length:**

Between 1.078 inches and 1.110 inches

**Body Width:**

Between 0.390 inches and 0.422 inches

**Body Height:**

Between 0.609 inches and 0.641 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.109 inches and 0.119 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.401 inches and 0.411 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.915 inches

**Actuator Roller Diameter:**

Between 0.172 inches and 0.204 inches

**Actuator Roller Width:**

Between 0.172 inches and 0.204 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0