# NSN 5930-00-996-1605

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-996-1605

### Body Style:

Hole mounted

#### **Overall Length:**

1.485 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.870 inches and 0.880 inches

#### **Overall Height:**

1.431 inches

#### **Overall Width:**

0.406 inches

#### **Body Length:**

Between 1.078 inches and 1.110 inches

#### **Body Width:**

Between 0.390 inches and 0.422 inches

#### **Body Height:**

Between 0.609 inches and 0.641 inches

#### Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

Between 0.109 inches and 0.119 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.401 inches and 0.411 inches

#### Actuator Style:

Roller arm

#### **Actuator Free Position Height:**

0.915 inches

#### Actuator Roller Diameter:

Between 0.172 inches and 0.204 inches

#### Actuator Roller Width:

Between 0.172 inches and 0.204 inches

#### Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

14.0 ounces

# NSN 5930-00-996-1605

Sensitive Switch - Page 2 of 2



# Actuator Movement:

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

# Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A053a0