## NSN 5930-00-996-7510

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-996-7510

**Thread Class:** 

3b single pressure connection

**Overall Length:** 

3.250 inches

**Overall Width:** 

3.570 inches

**Body Diameter:** 

2.400 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.220 inches and 0.250 inches

**Distance Between Mounting Facility Centers:** 

Between 2.990 inches and 3.010 inches

**Pressure Switch Type:** 

Differential

**Mounting Method:** 

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

**Contact Action Stimulus:** 

Increase

Thread Size:

0.438 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

10.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:** 

6.00 actuation point inches of mercury and 3.00 deactuation point inches of mercury

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Cylindrical w/mounting lugs

## NSN 5930-00-996-7510

Pressure Switch - Page 2 of 2



T	'nr	ead	<b>Series</b>	Design	ator:

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0