NSN 5930-00-996-7510

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-996-7510

Thread Class:

3b single pressure connection

Overall Length:

3.250 inches

Overall Width:

3.570 inches

Body Diameter:

2.400 inches

Unthreaded Mounting Hole Diameter:

Between 0.220 inches and 0.250 inches

Distance Between Mounting Facility Centers:

Between 2.990 inches and 3.010 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

6.00 actuation point inches of mercury and 3.00 deactuation point inches of mercury

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

NSN 5930-00-996-7510

Pressure Switch - Page 2 of 2



T	'nr	ead	Series	Design	ator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0